

HTRC Corrugated Pipe Couplings

Large diameter corrugated pipe couplings 10" to 60"

Technical Data

Ultimate Shear Resistance - .012" (12mil) 300 series stainless steel shear ring offers greater sealing force on corrugated pipe and ensures a water tight seal is maintained.

Ultimate Pipe Alignment - Due to the thickness and strength of the shear ring, you are assured consistent pipe alignment against shear forces from soil compaction, shifting and settling.

Ultimate Sealing High Torque Clamps - 301 series stainless steel **High Torque Clamps**, offering greater sealing power and excellent corrosion resistance.

Ultimate Sealing Gasket - The flexible PVC gasket has a smooth inside surface providing greater sealing performance than ribbed rubber gaskets. The smooth internal wall of the gasket makes contact 360° over its entire length. This equates to a larger sealing surface and a higher coefficient of friction, providing maximum sealing capabilities as well as preventing slippage under the weight of shear forces.




Corrugated Polyethylene to Plastic

Corrugated Polyethylene to Corrugated Polyethylene

	A	B	C
Part Number	in.	in.	in.
*1070-10-8HTRC	11.6	8.4	6.0
*1070-1010HTRC	11.6	10.5	6.0
*1070-1210HTRC	14.4	10.5	10.0
*1070-1212HTRC	14.4	12.5	10.0
*1070-1515HTRC	17.7	15.3	10.0
*1070-1818HTRC	21.3	18.7	10.0
*1070-2424HTRC	28.1	24.8	10.0
*1070-3030HTRC	35.4	31.5	10.0
*1070-3636HTRC	41.6	39.4	10.0
*1070-4242HTRC	47.7	44.5	10.0
*1070-4848HTRC	54.1	50.8	10.0

	A	B	C
Part Number	in.	in.	in.
1071-1010HTRC	11.6	11.6	6.0
1071-1212HTRC	14.4	14.4	10.0
1071-1515HTRC	17.7	17.7	10.0
1071-1818HTRC	21.3	21.3	10.0
1071-2424HTRC	28.1	28.1	10.0
1071-3030HTRC	35.4	35.4	10.0
1071-3636HTRC	41.6	41.6	10.0
1071-4242HTRC	47.7	47.7	10.0
1071-4848HTRC	54.1	54.1	10.0
1071-5454HTRC	61.0	61.0	10.0
1071-6060HTRC	66.8	66.8	10.0



Additional sizes available upon request

* Insert Bushing included