





300 S. DAYTON ST. DAVISON, MI 48423 PH: 810-653-9626 FAX:810-654-2616

Part Weight	10.00 lbs.	TC
Min/Max Temp.	-30/140 Degrees F	.X=
Pressure Tested	4.3 PSI	
Material	Flexible PVC 60 Duro Shore A	A
Installation Torque	60" Lbs.	UNLESS (
Conforms to ASTM	D5926, C1173	LINUTO
Box Quantity		INCHI
Clamps used	300 Series	
I '		2DD AND

OLERANCES: Fractional ±

 $.XX = \pm .060$ $.XXX = \pm .032$ ANG.= $\pm 0.5^{\circ}$ S OTHERWISE SPECIFIED

1051-1615

Coupling 16" DI/AC x 15" Cast Iron/Plastic

SCALE not to scale D. Brady 3RD ANGLE PROJECTION CHECKER: DATE: 1/17/2011 SHEET 1 OF 1 DO NOT SCALE DRAWING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.