









| | tolerances: | Part Weight | 19.12 lbs. | Installation Torque | 120 in Ibs | UNITS: | SIZE: | DESIGNER: | | SCALE: |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------|-----------------|---------------------------------|---------------------|----------------------|----------------------|-----------|-----------|------------|--------------|
| ITIAL Ed in This RTY of Iction in Ut The NCO, INC. | .X= Fractional \pm .XX= \pm .06 ANG.= \pm 3° UNLESS OTHERWISE SPECIFIED | Min/Max Temp. | -30/140 Degrees F | Conforms to ASTM | D5926, C1173 | INCHES A | | ١ | I. Goddard | not to scale |
| | | Pressure Tested | | Clamps used | 300 Series Stainless | 3RD ANGLE PROJECTION | | 0.150/52 | DATE: | |
| | | Material | Flexible PVC 60 Duro Shore A | Box Quantity | 2 | do not scal | E DRAWING | CHECKER: | 1/18/2016 | SHEET 1 OF 1 |

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN DRAWING IS THE SOLE PROPERTY O FERNCO, INC. ANY REPRODUCTIO PART OR AS A WHOLE WITHOUT TH WRITTEN PERMISSION OF FERNCO, IS PROHIBITED.

Coupling 21" Clay x 21" Clay