Before You Do-It-Yourself, **Prepare Yourself.**

To select the appropriate PlumbQwik product you need to know the actual size of the pipe(s) you are working with. Simply measure the outside circumference of the pipe with a cloth tape measure or piece of string. Use this chart to convert pipe circumference to actual pipe size.

PIPE CIRCUMFERENCE	ACTUAL PIPE SIZE	PIPE CIRCUMFERENCE	ACTUAL PIPE SIZE
4¼″ to 5¼″	1¼″	13" to 14¼"	4″
51/8" to 6"	1½″	165/8″ to 17¼″	5″
65/8" to 71/2"	2″	19 ⁵ /8″ to 20 ⁷ /8″	6″
97/8″ to 11″	3″		

If you are working with cast iron soil pipe commonly used in drains, it is also important to know the pipe grade. Three grades are used: XH-Extra Heavy (with larger hub); SV-Service Weight; and NH-No Hub (with plain end). Pipe grade (XH or SV) is marked on the hub. No hub, of course, has no hub; the end must be joined using a PlumbQwik coupling. XH and SV hubs require different PlumbQwik donuts.

Be sure you check the PlumbQwik product label for all application and installation information. This is essential to ensure a proper pipe connection.

PlumbQuvik S Fernco

SHOWER DRAIN CONNECTOR



Sizes to connect 2" D.W.V

plastic, Schedule 40, steel

or extra heavy cast iron


pipe to most common

shower drain bodies.

PSD Series

Connect drain pipe to shower drain bodies.

- Ideal for new installations, alterations or repairs.
- Fast, easy installation. No special tools, gluing or caulking required.



hubs.

DONUTS



- Size-to-size connections or reducing size connections.
- Impervious to soil conditions, sewage & normal sewer gas.
- Fast, easy installation hammer & block wood are all you need.
- Sizes: 1-1/2" to 4"



PUC Series

Easy connection for dishwasher, laundry tray pumps, air conditioners and other condensate drains and flexible hoses.

- Simple press-fit installation no tools required.
- Sizes to connect 1", 3/4", or 1/2" CPVC and copper pipe to 1-1/2" D.W.V. Sch. 40 plastic sockets.



PHG Series

Prevents accidental

washer-hose spills -

Holds washing machine

hose securely in

standpipe drains.

HOSE GRIP CONNECTOR



- Fits both 2" and 1-1/2" standpipes and most washing machine hoses from 1" to 1-7/16".
- Built from strong, flexible PVC for years of trouble-free use.

DOWNSPOUT CONNECTOR


- Stretches easily over downspout and drain pipes to seal out debris and pests.
- Install without tools, glues, or cement.
- Sizes to connect 3" or 4" drain pipe to common rectangular, round, & square downspouts.

OWIK CAPS



- Perfect for temporary or permanent use - and is reusable.
- To install, just tighten with a screwdriver.
- Sizes for all drain. waste and vent pipe materials of 1-1/2" to 6".







PDSC Series


Connect aluminum, steel or plastic downspouts to cast iron, spiral, corrugated or plastic drain pipes.



PQC Series

Seal plain-end pipe ends during repair, alterations, clean-out or new installations.

Flexible Drain Pipe Connectors and Adapters









A Houseful of Owik Solutions to Pipe Connection Problems.

Now you can make uncommonly tough plumbing jobs uncommonly easy with PlumbQwik Drain Pipe Connectors. There's just no faster, easier way to repair or alter sewer, drain, waste and vent systems, anywhere in your home.

PlumbOwik connectors are made of a specially formulated PVC, not rubber. The material won't rust or corrode and is highly resistant to caustic chemicals—even those used in drain cleaners.

Installation is a breeze. A common screw driver is all you need. Easy-to-follow instructions are included with every connector.

PlumbQwik products adapt to most drain pipe material, including copper, iron, plastic, lead and steel. Connect pipes of different materials and sizes, in minutes, above or below ground.

Qwik, Easy, **Flexible**

FLEXIBLE COUPLINGS

1056 Series

Connects Cast Iron, Plastic, Copper, Steel or Lead Pipes.

- Positively seals any drain connection.
- Stainless steel clamps and housings.

1070 Series

Connects Corrugated Polyethylene to Plastic Pipe.

- Ideal for drainage & irrigation systems. Positively seals any drain connection.
- Stainless steel clamps and housings.

PROFLEX

No Hub

Connect Hubless C.I.

Pipes & Fittings.

· Positively seals any

drain connection.

Stainless steel clamps

and housings.



Proflex Shielded Couplings

For Cast Iron to Plastic. Steel or XH Cast Iron.



FLEXIBLE TEES & ELLS

POT & POL Series

Replace fittings that have been removed for alteration or repair.



- For all common household drain, waste and vent pipes.
- Ideal for in-wall or limited space connections because they are exceptionally flexible & extra long.
- Ideal replacement for fittings cut out during alterations or repairs.
- Sizes: 1-1/2", 2", 3", 4"

TUBULAR DRAIN CONNECTOR

PTC Series

Extend, alter or repair any

combination of 1-1/4" or 1-1/2" brass or plastic tubular drain pipe.

- Leak-free seals on sink, lavatory, garbage disposal and laundry tub drainage systems.
- Fast simple installation with screwdriver.
- · Appealing grey color.





- Provides reliable leak-free seal.
- One size fits every application.
- · Installs in seconds with common screwdriver.
- · Appealing grey color.

DRAIN TRAP CONNECTOR



- Perfect for repairs alterations or new installations.
- Fast simple installation with a screwdriver.
- Appealing grey color.

www.fernco.com









DISHWASHER DRAIN PDWC Series

Connects dishwasher drain hose to sink drains or garbage disposers.



REPAIR FLANGE

PSF Series

For the repair of broken toilet flanges.

- Stop wobbly, leaking toilets.
- Save time and money by eliminating the need to replace broken flanges.
- Fits all cast iron, plastic, and brass water closet flanges.



PDTC Series

Connect 1-1/2" or 2" drain pipe to 1-1/4" or 1-1/2" drain traps.



- Flexible PVC adjusts to misaligned pipes.
- Just squeeze to clean no drain tools or drain cleaner chemicals needed.
- Appealing grey color.
- Resists freeze damage.

FLEXIBLE OWIK TRAP

PFT Series

Replace any combination of 1-1/4" or 1-1/2" plastic or metal tubular traps.

> For plastic to plastic, metal to metal, or plastic to metal connections.

