No-Hub Couplings

Replace the less-efficient hub & spigot material and connect no-hub cast iron pipe with Fernco's No Hub Coupling.



Standard No-Hub


Couplings conform to CISPI 310. Couplings comply with ASTM C 1277. Gaskets are made from an elastomeric compound that meets the requirements of ASTM C 564.

Medium Duty No-Hub

Couplings conform to CISPI 310, Factory Mutual CN 1680. Couplings comply with ASTM C564, ASTM C1540, IAPMO file #3198, Commonwealth of Mas-sachusetts CMR-248 and City of New York MEA 253-98-E. Gaskets are made from an elastomeric compound that meets the requirements of ASTM C564.


Heavy Duty No-Hub

Couplings conform to CISPI 310, Factory Mutual FM 1680. Couplings comply with ASTM C564, ASTM 1277, IAPMO file #3198, Commonwealth of Mas-sachusetts CMR-248 and City of New York MEA 253-98-E. Gaskets are made from an elastomeric compound that meets the requirements of ASTM C564.



Bi-Directional Shield Design

The shield adjusts to a variety of a pipes diameters and circumferences to eliminate leaks. The bi-directional corrugations seal pressure in both parallel and transverse patterns on the gasket and pipe to provide a positive, reliable seal.




Floating Eyelet Design

Fastening the clamps to the shield, the floating eyelets allow the clamp band and shield to move independently. This freedom prevents the shield from crimping and future leakage.



Specially Beaded Gasket

Meeting the requirements of ASTM C564, the beaded gasket consists of an elastomeric compound with strategically positioned grooves and beads. When tightened, the shield attaches to the grooves and beads to provide exceptional sealing pressure and holding power.



Interlocking Clamp Design

The clamps feature a one-piece screw housing that mechanically interlocks to the band. This design eliminates leak paths that occur in staked or welded clamps.

Environmental Commitment

Fernco® Inc.

United States
PH: 810-653-9626
FX: 810-653-8714

www.fernco.com

Canada
PH: 519-332-6711
FX: 519-332-8610



Standard No-Hub Couplings

5/16" hex-head screw applies 60 in.-lbs. of installation torque to the band/shield assembly.

PART NUMBER	SIZE	CLAMPS PER COUPLING	INSTALL TORQUE (inch pounds)	CARTON QUANTITY*	WEIGHT EACH LBS.	CARTON WEIGHT	UPC NUMBER
NH-150	1-1/2"	2	60	100	.22	23.00	0 1857800 075 9
NH-22	2"	2	60	100	.263	26.30	0 1857800 076 6
NH-33	3"	2	60	100	.35	35.00	0 1857800 077 3
NH-44	4"	2	60	100	.41	41.00	0 1857800 078 0
NH-55	5"	4	60	20	.85	17.00	0 1857800 080 3
NH-66	6"	4	60	20	.98	19.60	0 1857800 081 0
NH-88	8"	4	60	10	1.40	14.00	0 1857800 109 1
NH-1010	10"	4	60	10	1.79	17.90	0 1857800 147 3
NH-1212	12"	6	120	12	2.72	32.64	0 1857800 423 8
NH-1515	15"	6	120	6	3.63	21.78	0 1857800 424 5
			REDUCING SIZE NO-HUB				
NH-215	2" x 1-1/2"	2	60	100	.343	34.30	0 1857800 079 7
NH-32	3" x 2"	2	60	100	.58	58.00	0 1857800 134 3
NH-42	4" x 2"	2	60	60	1.01	60.60	0 1857800 135 0
NH-43	4" x 3"	2	60	60	.79	47.40	0 1857800 136 7



Medium Duty No-Hub Couplings

5/16" hex-head screw applies 80 in.-lbs. of installation torque to the band/shield assembly.

PART NUMBER	SIZE	CLAMPS PER COUPLING	INSTALL TORQUE (inch pounds)	CARTON QUANTITY*	WEIGHT EACH LBS.	CARTON WEIGHT	UPC NUMBER
MD-150	1-1/2"	4	80	60	.37	22.20	0 1857800 544 0
MD-22	2"	4	80	75	.45	33.75	0 1857800 545 7
MD-33	3"	4	80	48	.56	26.88	0 1857800 546 4
MD-44	4"	4	80	48	.71	34.08	0 1857800 547 1
MD-55	5"	6	80	15	1.13	16.95	0 1857800 548 8
MD-66	6"	6	80	15	1.37	20.55	0 1857800 549 5
MD-88	8"	6	80	15	1.77	26.55	0 1857800 550 1
MD-1010	10"	6	80	12	2.28	27.36	0 1857800 551 8



Heavy Duty No-Hub Couplings

3/8" hex-head screw applies 80 in.-lbs. of installation torque to the band/shield assembly.
Provides an ultimate torque rating exceeding 100 in.-lbs. and heavier gauge stainless steel.

PART NUMBER	SIZE	CLAMPS PER COUPLING	INSTALL TORQUE (inch pounds)	CARTON QUANTITY*	WEIGHT EACH LBS.	CARTON WEIGHT	UPC NUMBER
HD-150	1-1/2"	4	80	60	.40	24.00	0 1857800 384 2
HD-22	2"	4	80	75	.45	33.75	0 1857800 385 9
HD-33	3"	4	80	48	.60	28.80	0 1857800 386 6
HD-44	4"	4	80	48	.74	35.52	0 1857800 387 3
HD-55	5"	6	80	15	1.25	18.75	0 1857800 388 0
HD-66	6"	6	80	15	1.34	20.10	0 1857800 389 7
HD-88	8"	6	80	15	1.75	26.25	0 1857800 390 3
HD-1010	10"	6	80	12	2.00	24.00	0 1857800 391 0

** Cartons may be broken if necessary. UPC bar codes are available for an additional charge.*