SAFETY DATA SHEET

SECTION 1: Identification

Trade Name: MAINSTAY DS5 FAST SET PART B

Emergency phone

Supplier and manufacturer:

MADEWELL PRODUCTS CORPORATION

7561 INDUSTRIAL COURT ALPHARETTA GA 30004 PHONE: 770-475-8199 FAX: 770-475-8167 PERS 800-633-8253

SECTION 2: Hazard(s) Identification

GHS Ratings:

Skin corrosive 1C		Destruction of dermal tissue: Exposure < 4 hours Observation
		< 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after
		exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Carcinogen	1A	Known Human Carcinogen Based on human evidence

GHS Hazards

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H350	May cause cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
	• •
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash hands thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see instructions on this label)
P363	Wash contaminated clothing before reuse
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P405	Store locked up

SDS for: DS5 B FAST SET GRAY

Signal Word: Danger



SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %	
polyoxy(methyl-1,2-ethanediyl),alpha-hydro-omega- hydroxy-,ether with 2.2-bis	72244-98-5	40.00% - 50.00%	
QUARTZ	14808-60-7	20.00% - 30.00%	
TITANIUM DIOXIDE	13463-67-7	10.00% - 20.00%	
TALC	14807-96-6	5.00% - 10.00%	
SYNTHETIC AMORPHOUS, PYROGENIC SILICA	112945-52-5	1.00% - 5.00%	

SECTION 4: First Aid Measures

Inhalation: Move person to fresh air. Get medical attention if symptoms develop.

Eye contact: Bathe the eye with running water for at least 15 minutes, lifting upper and lower eyelids. Get medical attention if symptons persist.

Skin contact: Drench the affected area immediately with plenty of water, remove contaminated clothing. Wash thoroughly with soap and water for at least 15 minutes. Seek medical attention if irritation, rash, or other adverse effects occur.

Ingestion: Rinse mouth then drink plenty of water. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention/advice if you feel unwell.

Most important symptoms and effects, both acute and delayed

Skin irritation. May cause redness and pain. May cause allergic reactions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

SECTION 5: Fire Fighting Measures

Flash Point: N/A

LEL: N/A UEL: N/A

Exginguishing media:Carbon dioxide, alcohol resistant foam, dry chemical, water fog; use water spray to cool fire-exposed containers. Do not use direct water stream which may spread fire.

Unusual fire/ expl. hazards: Exposure to decomposition products may be harmfult to health; combustion products may include but are not limited to: carbon monoxide, carbon dioxide, phenolics; smoke may contain particles of the original material as well. Prevent fire-fighting waters from entering sewer or waterways.

Fire equipment:Use protective fire fighting clothing and positive pressure self-contained breathing apparatus to protect against potential harmful and/or irritating fumes. Do not use high volume water jet as this may spread the area of the fire.

SECTION 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Isolate area; ensure adequate ventilation; use appropriate personal protection equipment; avoid breathing mist, vapors, spray; avoid contact with skin, eyes and closthing; keep unnecessary and unprotected personnel from entering the involved area.

Environment precautions;

Prevent contamination of soil and water. Prevent from spreading or entering into drains ditches, waterways by using sand, earth or appropriate barriers.

Method and material for containment and cleaning up

Absorb with sand, diatomaceous earth or universal binders and collect into suitable disposal container. Dispose of in accordance with applicable local and federal environmental control laws and regulations.

SDS for: DS5 B FAST SET GRAY Page 2 of 6

Printed: 8/9/2022 at 12:10:50PM

SECTION 7: Handling and Storage

Precautions for safe handling

Ensure adequate ventilation of workplace and storage areas; avoid skin contact; do not breathe mist, vapors, spray; use recommended personal protective equipment; wash thoroughly after handling. Do not eat, drink or smoke in the work area. Avoid use of electric band heaters (failures of such heaters have been reported to cause drums of liquid epoxy resin to explode and catch fire). Never apply a direct flame to any container of product.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Keep away from incompatible materials, Keep container tightly closed. Recommended storage temperature: 10-35C (50-95F)

SECTION 8: Exposure Controls/Personal Protection						
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits			
polyoxy(methyl-1,2- ethanediyl),alpha-hydro- omega-hydroxy-,ether with 2.2-bis 72244-98-5	Not Established	Not Established	Not Established			
QUARTZ 14808-60-7	.1MG/M3	.025MG/M3 RESPIRABLE FRACTION	Not Established			
TITANIUM DIOXIDE 13463-67-7	TWA 15 MG/M3	TWA 10MG/M3	Not Established			
TALC 14807-96-6	2MG/M3 RESPIRABLE FRACTION	2MG/M3	Not Established			
SYNTHETIC AMORPHOUS, PYROGENIC SILICA 112945-52-5	15 MG/M3 TOTAL DUST 5 MG/M3 RESPIRABLE	10 MG/M3 INHALABLE 3 MG/M3 RESPIRABLE	Not Established			

Occupational exposure limits: OSHA/PEL: None established.

Ensure adequate ventilation through local exhaust.

Follow good industrial workplace practices; do not eat, drink or smoke wihile handling; wash hands before breaks and at end of workshift; follow recommendations in this SDS.

Eye/face protection

Use safety glasses with side shields.

Skin protection

Wear impervious clothing as necessary to protect against product contact,. Necessity for boots, apron, face shield, etc. will be dependent on any hazards presented in the work process.

Respiratory protection

Although no exposure limits have been established, respiratory protection may be of use if any respiratory irritation or discomfort is noted; if the material is processed at elevated temperatures without adequate ventilation it may be necessary to wear an air-purifying respirator with organic vapor cartridge; respirator use should follow the guidelines of an established respiratory protection program in compliance with 29CVF1910.134.

Hand protection

Wear nitrile rubber, nitrile, neoprene, PVC or other suitable impervious gloves. Gloves selected musthave a breakthrough rating appropriate for the work shift.

Other protective equipment

Teh type and degree of personal protective equipment appropriate willk depend on the specific work operation. Eye wash stations and emergency showers should be available.

SDS for: DS5 B FAST SET GRAY Page 3 of 6

SECTION 9: Physical and Chemical Properties

Physical state: liquid

Initial Boiling Point: Not determined Melting Point: Not applicable Type of Odor: Slight mercaptan odor Odor Threshold: Not determined Flash Point: 93.3C (199F) (PMCC) Vapor Pressure: not available Evaporation Rate: Not available

Decomposition Temperature: Not available

Solubility in Water: Insoluble

pH: Not available

Octanol/Water Partition Coefficient (log Pow): Not available

Autoignition Temperature: Not available

Specific Gravity: 1.04-1.08

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No dangerous reaction is known uder normal use and storage conditions.

Stability: Stable under normal use and storage conditions.

Possibility of hazardous reactions: Conditions to avoid: Elevated temperatures Materials to avoid: Strong oxidizing agents

Hazardous decomposition products: By fire: carbon monoxide, aldehydes

SECTION 11: Toxicological Information

Mixture Toxicity Component Toxicity

Skin: Causes skin irritation; may cause sensitization; once sensitized, a severe allergic reaction may ocur when subsequently exposed to very low levels.

Eyes: Causes serious eye irritation; pain, irritation, watering, redness.

Ingestion: Low toxicity; incidental ingestion of small amounts not anticipated to be harmful.

Inhalation: Low volatility; not expected to be a significant route of exposure.

Specific Target Organ Toxicity - single exposure (STOT-se): Not classified based on available data. Specific Target Organ Toxicity - repeated exposure (STOT-re):Not classified based on available data.

Effects of Overexposure

Carcinogenicity: Not Classified based on available date., Not listed by IARC, NTP, OSHA

Potential Chgronic Health Effects: 90 day (rat) Repeated Dose Oral Toxicity Study NOAEL: 50 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

SDS for: DS5 B FAST SET GRAY Page 4 of 6 Chronic toxicity to aquatic life Harmful with long lasting effects.

Persistence and degradability

No data available

Mobility in soil

No data availabel

Component Ecotoxicity

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal: Do not dump to ground, sewers or wtercourses. Reuse uncontaminated material wehn possilbe. All methods of disposal must be in compliance with all applicable federal, state and local environmental control laws and regulations. Weste characterization according to RCRA guidelines and compliance wiyth applicable laws are the responsibility solely of the waste generator. **Container disposal:**Containers should be drained of all residual product prior to disposal; empty/clean containers should be recycled; incinerate or landfill when recycling is not feasible.

SECTION 14 - TRANSPORT INFORMATION

Shipping description

IATA-DGR: UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-TRIS(DIMETHYL AMINOMETHYL) PHENOL, BIS

(DIMETHYLAMINO)METHYL PHENOL)

CLASS: 8

Packing Group: PG III

Classification of the material for transportation purposes may vary by container volume as well as regional or country variations in regulations.

SECTION 15 - REGULATORY INFORMATION

Safety, health and environmenbtal regulations/legislation specific for the substance or mixture

SARA Title III Section 311/312 (40CFR370): Yes

SARA Title III Section 313 (40CFR372): No reportable components CERCLA Statue (40CFR302): No reportable quantity components

TSCA Inventory Status: Not regulated Canadian DSL Status: Reported/included

EU Risk Phrases

Safety Phrase

SECTION 16 - OTHER INFORMATION

HMIS ratings:

Health 2

Flammability 1

Reactivity 0

(Personal protective equiment selection is best assigned by the user after performing a hazard assessment on the product as it is to be used in the specific work process.)

This information or recommendations contained herein are based on standard product and are proprietary and furnished solely for the use of our customers. This information is provided in good faith and believed to be true and accurate as of the date shown below; however since we have no control over the use conditions or production processes of parties using this product, Madewell Products Corp. cannot accept responsibility for loss, injury or other damages resulting from the use of the product or this or any other information

SDS for: DS5 B FAST SET GRAY Page 5 of 6

provided by us. Therefore, no guarantees of any kind expressed or implied are made by Madewell Products Corp. with regard to any of their products. Users are advised to perform their own tests and hazard assessments to determine the safety, suitability and relevance of applicable law to the product as it is to be used by them.

Reviewer Revision

Date Prepared: 8/9/2022

SDS for: DS5 B FAST SET GRAY Page 6 of 6

Printed: 8/9/2022 at 12:10:50PM